

 **BELSHINA**

# Robust & Resilient Off-The Road Tyre



We guarantee high quality of all our products since we have the latest machinery, best experts, we implement the latest achievements of science and technology and entire production cycle is streamlined. Due to their reliability, durability and comfort tyres from Belarus have gained high reputation with FSU, European and overseas consumers.



Tyre size	27.00-49
Type	
Tube type	TL
Tubeless	
Tread pattern	Rock
Ply rating	48
Application	Dump truck BelAZ 75-80 tonnage and similar

Rim recommended	19.50-35/4.0
Sectional width, mm	765

**FT-115**

Max load per tyre, index	220
Max load per tyre, kg	25000.0
Internal pressure, kPa	575
Max speed, index	B
Max speed, Km/h	50
Single (O) Dual (S)	0
TKPH	355



Tyre size	33.00-51
Type	
Tube type	TL
Tubeless	
Tread pattern	Rock
Ply rating	58
Application	Dump truck BelAZ 120-130 tonnage and similar

Rim recommended	24.00-51/5.0
Sectional width, mm	955

**FT-116AM2**

Max load per tyre, index	230
Max load per tyre, kg	35500.0
Internal pressure, kPa	575
Max speed, index	B
Max speed, Km/h	50
Single (O) Dual (S)	0
TKPH	492



Tyre size	40.00-57
Type	
Tube type	TL
Tubeless	
Tread pattern	Rock
Ply rating	60
Application	Dump truck BelAZ 180-200 tonnage and similar

Rim recommended	29.00-57/6.0
Sectional width, mm	1140

**FT-117**

Max load per tyre, index	244
Max load per tyre, kg	50500.0
Internal pressure, kPa	500
Max speed, index	B
Max speed, Km/h	50
Single (O) Dual (S)	0
TKPH	657



Tyre size	21.00-35
Type	
Tube type	TL
Tubeless	
Tread pattern	Rock
Ply rating	36
Application	Dump truck BelAZ 45.4 tonnage and similar

Rim recommended	15.00-35/3.0
Sectional width, mm	572

**Bel-51**

Max load per tyre, index	197
Max load per tyre, kg	12850.0
Internal pressure, kPa	550
Max speed, index	B
Max speed, Km/h	50
Single (O) Dual (S)	0



Tyre size	18.00-25
Type	
Tube type	TT
Tubeless	
Tread pattern	Rock
Ply rating	32
Application	Dump truck BelAZ 30 tonnage and similar

Rim recommended	13.00-25/2.5
Sectional width, mm	498

**Bel-76M**

Max load per tyre, index	183
Max load per tyre, kg	8750.0
Internal pressure, kPa	600
Max speed, index	B
Max speed, Km/h	50
Single (O) Dual (S)	0



Tyre size	35/65-33
Type	
Tube type	TL
Tubeless	
Tread pattern	Rock
Ply rating	30
Application	Bulldozers, front loadersload capacity 10-20t

Rim recommended	28.00-33/3.5
Sectional width, mm	-

**Bel-283**

Max load per tyre, index	214
Max load per tyre, kg	21200.0
Internal pressure, kPa	425
Max speed, index	A2
Max speed, Km/h	10
Single (O) Dual (S)	0

**STAMFORD TYRES**

**Stamford Tyres International Pte Ltd**  
**Mining Department**

21A Lok Yang Way, Jurong, Singapore 628635 Tel: (65) 6268 4438 Fax: (65) 6262 1027  
 Website: www.stamfordtyres.com Email: mining@stamfordtyres.com