

Sumo Steel Wheels



For Tube Type



Available Sizes & Specification

Wheel Type	Bolt Hole				Center Hole Diameter	Thickness mm		Offset	Fitted Tyre
	Number	Diameter	Type	P.C.D		Rim	Disc		
5.50F-16 BB	5	29	JSR22	203.2	146		8	115	7.00-16
5.50F-16 BD	5	32.5	JSR22	2.03.2	146		8	115	7.00-16
7.00T-20	8	32.5	JSR22	285	221		8	162	9.00-20
7.00T-20	10	26	JSR18	335	281		12	162	9.00-20
7.00T-20C	10	32.5	JSR22	285.75	221.5		12	162	9.00-20
7.00T-20G	8	26	JSR18	275	221		12	155	9.00-20
7.50V-20L	8	32.5	JSR22	285	221		12	165	10.00-20
7.50V-20B	10	26	JSR18	335	281		12	162	10.00-20
7.50V-20J	10	32.5	JSR22	285.75	221.5		12	162	10.00-20
7.50V-20F	10	26	ISO	335	281		12	165	10.00-20
7.50V-20G	8	27	JSR18	275	221		12	155	10.00-20
8.00V-20B	10	26	JSR18	335	281		14	175	11.00-20
8.00V-20A	10	32.5	JSR22	285.75	221.5		14	175	11.00-20
8.00V-20C	8	32.5	JSR22	285	165		14	175	11.00-20


For Tubeless



Available Sizes & Specification

Wheel Type	Bolt Hole				Center Hole Diameter	Thickness mm		Offset	Fitted Tyre
	Number	Diameter	Type	P.C.D		Rim	Disc		
6.00HCx17.5	6	32	JSR22	222.25	164	5	9	127	8R17.5
6.00A17.5	5	29	JSR22	203.2	145	5	9	127	8R17.5
7.5Ax22.5	8	32.5	JSR22	285	221	6	13.5	162	10R22.5
8.25x22.5	10	26	ISO	335	281	7	13.5	165	11R22.5
8.25Bx22.5	10	26	JSR18	335	281	7	13.5	165	11R22.5
8.25CBx22.5	10	32.5	JSR22	285.75	221.5	7	13.5	168	11R22.5
8.25HAX22.5	8	32.5	JSR22	285	221	7	13.5	165	11R22.5
9.00Gx22.5	10	26	ISO	335	281	7	13.5	114	12R22.5 315/80R22.5
9.00x22.5	10	26	ISO	335	281	7	13.5	175	12R22.5
9.00Bx22.5	10	26	JSR18	335	281	7	13.5	175	12R22.5
9.00H22.5	10	26	JSR18	335	281	7	13.5	114	12R22.5
6.75Bx22.5	8	32.5	JSR22	285	221	7	12	142	9R22.5
8.25x19.5	10	26	JSR18	225	176	7	12	148	285/70R19.5
6.00Cx17.5	10	32	JSR22	224	171	6	13.5	127	8R17.5
6.00Gx17.5	5	32.5	JSR22	203.2	146	5	9	115	8R17.5
6.00Hx17.5	5	32.5	JSR22	203.2	134	5	9	115	8R17.5
6.00Jx17.5	5	32.5	JSR22	222.25	134	5	9	115	8R17.5

Industrial Wheels



Available Sizes & Specification

Wheel Type	Bolt Hole				Center Hole Diameter	Thickness mm		Offset	Fitted Tyre
	Number	Diameter	Type	P.C.D		Rim	Disc		
5.50Fx12	4	14	B90	127	92.7	4	4	0	
6.00Fx14	4	14	B90	127	92.7	4	4	0	
6.00Fx14	5	13.5	H1	139.7	101.6	4	4	0	
6.00Fx14.5	5	14	B90	139.7	102	4	4	0	

Agricultural Wheels



Available Sizes & Specification

Wheel Type	Bolt Hole				Center Hole Diameter	Thickness mm		Offset	Fitted Tyre
	Number	Diameter	Type	P.C.D		Rim	Disc		
4.50Ex16	5	15	A	139.7	110	4	6	20	6.50-16
5.50Fx16	6	17	A	180	141	4	6	22	7.50-16
5.50Fx20	5	19	H3	175	135	4	8	25	7.50-20
W7x20	8	17	A	152	108.5	4	6	9	8.30-20
W7x24	6	15	A	165	130	4	8	0	8.30-24
W8x24	6	20	C90	165	120	4	6	120	9.50-24
W9x20	6	16.5	A	285	250.5	4	7	104	11.2-20
W10x28	8	16.5	A	330	290.5	4	9	59.5	12.4-28
W12x24	8	16.5	A	330	290.5	4	9	6	13.6-24
W12x38	8	19	A	203.2	203.2	5	10	22.1	13.6-38

Other Available Sizes

3.00Dx14	6.00x20	W10x24	W12x28	W13x26	W14Lx30	W16Lx24
3.00Dx16	9.00x15.3	W10x32	W12x32	W13x28	W14Lx34	W16Lx30
20Tx5.50F	9.00x24	W12x26	W12x30	W14Lx24	W15Lx38	W16Lx38

STAMFORD Tyres

19 Lok Yang Way, Jurong Singapore 628635 Tel: (65) 6268 3111 Fax: (65) 6264 0148 / 6264 4708

Website: www.stamfordtyres.com Enquiries: stipl@stamfordtyres.com